

MODEL

GC20638 系列

综合送料针杆离合双针平缝机

Two needle compound feed split needle bar lockstitch sewing machine

GC20638/-D

GC20638-25/-25D

GC20638-DQ

GC20638-DQZ



GC20638-D 自动剪线综合送料针杆离合双针平缝机

本机是专为汽车座垫行业而开发的新品。采用了分离式针杆装置的综合送料双针厚料平缝机。二根针杆既可同时工作，也可根据需要独立运动，使缝纫转角时更方便，线迹清晰。上下轴用滚珠轴承支撑，同步齿形带传动，柱塞式油泵自动润滑。由于采用综合送料方式，特别适宜于较厚的多层物料车缝，如皮革、泡沫塑料、化纤等几种不同材料的叠层缝纫，不会产生滑移和错位。是缝制汽车座垫、汽车布艺饰件、真皮或合成皮革类的鞋面、运动器材、办公家具、软垫、箱包等类似物品的高档设备。


GC20638-25/-25D 长臂针杆离合综合送料厚料平缝机适用于汽车座垫、汽车套、安全带、帐篷、降落伞、滑翔伞、船帆、沙发等大型物品的缝制。

GC20638-DQZ 直驱一体式自动剪线综合送料针杆离合双针平缝机

This machine is a new product specially developed for car seat industry, which is designed with split needle bar to be engaged or disengaged for convenient corner stitching, ball bearing for arm shaft and lower shaft, cog belt driving, plunger oil pump for automatic lubrication. With compound feeding mechanism, it is available for stitching multi-layer material of heavy weight, such as leather, foam plastics, synthetic fabric, etc and can avoid any displacement. It is a high class equipment for stitching car seats, fabric decorations in cars, shoe uppers of leather or synthetic leather, sports apparatus, office furniture, soft cushion, trunk, bag, etc.

GC20638-25/-25D Long arm compound feed split needle bar lockstitch sewing machine is available for stitching car covers, car seats, safety belts, tents, parachutes, gliding parachutes, sofa, sails and other large workpiece.

GC20638-DQZ Integrated direct drive Two needle compound feed split needle bar lockstitch sewing machine thread trimmer



主要技术参数 Main technical specifications

型号 Model	最高缝速 Max. sewing speed	线迹长度 Stitch length	针杆行程 Needle bar stroke	压脚提升 Presser foot lift	机针 Needle size	自动剪线 Auto trimmer	旋梭 Rotating hook	润滑方式 Lubrication	电动机 Motor	操作空间 Working space
GC20638	2000 r.p.m.	0-9 mm	33.4 mm	手动 / 膝控 By hand / knee	DP × 17 23°	○	立式大旋梭 Large hook	自动润滑 Auto lubricated	370 瓦缝纫机专用电机 1400 转 / 分 370W Clutch motor 1400 r.p.m.	254 × 100 mm
GC20638-D	2000 r.p.m.	0-9 mm	33.4 mm	7 / 13 mm	DP × 17 23°	★	立式剪线大旋梭 Large hook for trimmer	自动润滑 Auto lubricated	220 伏 550 瓦伺服电机 220V 550W Servo motor	254 × 100 mm
GC20638-DQ	2000 r.p.m.	0-9 mm	33.4 mm		DP × 17 23°	★	立式剪线大旋梭 Large hook for trimmer	自动润滑 Auto lubricated	220 伏 550 瓦伺服电机 220V 550W Servo motor	254 × 100 mm
GC20638-DQZ	2000 r.p.m.	0-9 mm	33.4 mm	手动 / 气动 By hand / Pneumatic	DP × 17 23°	★	立式剪线大旋梭 Large hook for trimmer	自动润滑 Auto lubricated	220 伏 850 瓦伺服电机 220V 850W Servo motor	254 × 100 mm
GC20638-25	1800 r.p.m.	0-9 mm	33.4 mm	7 / 13 mm	DP × 17 23°	○	大型旋梭 Large hook	手工润滑 Manual	370 瓦缝纫机专用电机 1400 转 / 分 370W Clutch motor 1400 r.p.m.	635 × 100 mm
GC20638-25D	1800 r.p.m.	0-9 mm	33.4 mm		DP × 17 23°	★	大型自动剪线旋梭 Large hook for trimmer	手工润滑 Manual	220 伏 550 瓦伺服电机 220V 550W Servo motor	635 × 100 mm

针间距 Needle gauge

GC20638 GC20638-D GC20638-DQ GC20638-DQZ 标准 8 mm 特殊 9.5 mm 8 mm (Standard) 9.5 mm (Special)
GC20638-25 GC20638-25D 标准 8 mm 特殊 6.4 mm 9.5 mm 8 mm (Shandard) 6.4 mm 9.5 mm (Special)

特殊规格针间距请在订货时指定
Please specify for special needle gauge when ordering