

MODEL

GC24608 系列

立柱式综合送料缝纫机

Post-bed compound feed lockstitch sewing machine

- GC24608-1L/1R
- GC24608-1LD/1RD
- GC24608-2/-2D
- GC24608-2Q/-2QZ
- GC24608-1LQ/1RQ
- GC24608-25R



GC24608-2QZ 直驱一体式立柱式综合送料缝纫机

本系列机型是海菱高台机的新产品，采用综合送料方式和立柱式缝台。
本系列机型根据缝制品的需要分双针、单针。单针机型又可分为左缝台和右缝台两种，以满足不同的需要，立柱式缝台使操作空间宽敞，缝料回转灵活，缝纫顺畅自如，线迹均匀美观；采用翻动式旋梭盖，使换取梭芯更方便。本系列机型最适合于缝制汽车座垫、箱包、皮靴及手提袋等产品。

- GC24608-1L/1R 单针立柱式综合送料平缝机 (左缝台 / 右缝台)
- GC24608-1LD/1RD 自动剪线单针立柱式综合送料平缝机 (左缝台 / 右缝台)
- GC24608-2 双针立柱式综合送料平缝机
- GC24608-2D 自动剪线双针立柱式综合送料平缝机
- GC24608-2Q/-2QZ 双针立柱式综合送料平缝机 (气动抬压脚、气动倒缝) / 直驱
- GC24608-1LQ/1RQ 单针立柱式自动剪线综合送料平缝机 (左缝台 / 右缝台) (气动抬压脚、气动倒缝)
- GC24608-25R 长臂型单针立柱式综合送料平缝机 (右缝台) (气动抬压脚、气动倒缝)

This machine series is a new product series of Highlead brand post bed lockstitch sewing machines. It is designed with compound feed mechanism and post bed. It has three sub models of single needle left-side stitching machine, single needle right-side stitching machine and two needle post bed compound feed machine, to meet different demands from the market. With the features of free stitching, beautiful stitches, easy bobbin changing, it is available for stitching car seat, bag and case, boots, hand bags, etc.

主要技术参数 Main technical specifications

型号 Model	最高缝速 Max. sewing speed	针杆行程 Needle bar stroke	线迹长度 Stitch length	压脚提升 Presser foot lift	压脚交互量 Presser foot alternation	机针 Needle size	缝台高度 Height of post-bed	气动倒缝 Pneumatic reverse feeding	气动抬压脚 Pneumatic foot lifting	自动剪线 Auto trimmer	操作空间 Working space	电动机 Motor	
GC24608-1L/1R	2000 r.p.m.	36 mm	0-7 mm	手动 / 膝控 By hand / knee	2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	○	○	○	250 × 284 mm	370 瓦缝纫机 专用电机 1400 转 / 分 370W Clutch motor 1400r.p.m.	
GC24608-2	2000 r.p.m.	36 mm	0-7 mm	8 / 16 mm	2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	○	○	○	250 × 284 mm	370W Clutch motor 1400r.p.m.	
GC24608-1LD/1RD	2000 r.p.m.	36 mm	0-7 mm	气动 16 mm Pneumatic	2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	★	250 × 284 mm	220 伏 550 瓦 伺服电机 220V/550W Servo motor	
GC24608-2D	2000 r.p.m.	36 mm	0-7 mm		2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	★	250 × 284 mm		
GC24608-1LQ/1RQ	2000 r.p.m.	36 mm	0-7 mm		2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	○	250 × 284 mm		
GC24608-2Q	2000 r.p.m.	36 mm	0-7 mm		2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	○	250 × 284 mm		
GC24608-2QZ	2000 r.p.m.	36 mm	0-7 mm		2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	○	250 × 284 mm		220 伏 850 瓦伺服电机 220V 850W servo motor
GC24608-25R	1600 r.p.m.	36 mm	0-7 mm		2-6 mm	DP × 17 22 [#] -24 [#]	178 mm	★	★	○	250 × 284 mm		220 伏 550 瓦伺服电机 220V 550W servo motor

针间距 Needle gauge	GC24608-2	GC24608-2D	GC24608-2Q	GC24608-2QZ	标准 Standard 8 mm	特殊 Special 9.5 mm
------------------	-----------	------------	------------	-------------	------------------	-------------------



- GC24608-1L/1R Single needle post-bed compound feed lockstitcher (Lift-side stitching bed / Right-side stitching bed)
- GC24608-1LD/1RD Single needle post-bed compound feed lockstitcher with thread trimmer (Lift-side stitching bed / Right-side stitching bed)
- GC24608-2 Twin-needle post-bed compound feed lockstitcher
- GC24608-2D Twin-needle post-bed compound feed lockstitcher with thread trimmer
- GC24608-2Q/-2QZ Twin-needle post-bed compound feed lockstitcher (Pneumatic foot lifter, Pneumatic reverse feeding) / Direct drive
- GC24608-1LQ/1RQ Single-needle post-bed compound feed lockstitcher with trimmer (Lift-side stitching bed / Right-side stitching bed) (Pneumatic foot lifter, Pneumatic reverse feeding)
- GC24608-25R Long arm single-needle post-bed compound feed lockstitcher (Right-side stitching bed) (Pneumatic foot lifter, Pneumatic reverse feeding)

特殊规格针间距请在订货时指定
Please specify for special needle gauge when ordering