

MODEL

GC24628-1 系列

立柱式综合送料针杆离合双针平缝机

Two needle post bed compound feed split needle bar lockstitch sewing machine

- GC24628-1
- GC24628-25
- GC24628-1Q
- GC24628-D

本机是海菱高台双针机系列中的新款，立柱式缝台，综合送料，分离式针杆机构。二根针既可同时工作，也可根据需要独立运动，使缝纫转角时更方便、线迹清晰、更适合圆弧面物料的缝纫。由于采用综合送料方式，特别适宜于较厚的多层物料之车缝。如皮革、泡沫塑料、化纤等几种不同材料的叠层缝纫，不会产生滑移和错位。是缝制汽车座垫、汽车布艺饰件、真皮或合成皮革类的鞋面、运动器材、办公家具、软垫、箱包等类似物品的高档设备。

- GC24628-1 立柱式综合送料针杆离合双针平缝机
- GC24628-25 长臂型立柱式综合送料针杆离合双针平缝机
- GC24628-1Q 立柱式综合送料针杆离合双针平缝机 (气动抬压脚、气动倒缝)
- GC24628-D 自动剪线立柱式综合送料针杆离合双针平缝机

This machine is a new product of Highlead brand post bed two needle lockstitch sewing machine series, which is designed with post bed, compound feeding mechanism and split needle bar mechanism. The two needles can be engaged or disengaged for convenient corner stitching and clear stitches, especially available for stitching on surfaces with radius. With compound feeding mechanism, it is available for stitching multi-layer material of heavy weight, such as leather, foam plastics, synthetic fabric, etc and can avoid any displacement. It is a high class equipment for stitching car seats, fabric decorations in cars, shoe uppers of leather or synthetic leather, sports apparatus, office furniture, soft cushion, trunk, bag, etc.

- GC24628-1 Twin-needle post bed compound feed split needle bar lockstitch sewing machine
- GC24628-25 Long arm two needle post bed compound feed split needle bar lockstitch sewing machine
- GC24628-1Q Twin-needle post bed compound feed split needle bar lockstitch sewing machine (Pneumatic foot lifter, Pneumatic reverse feeding)
- GC24628-D Twin-needle post bed compound feed split needle bar lockstitch sewing machine with auto trimmer

主要技术参数 Main technical specifications

型号 Model	最高缝速 Max. sewing speed	线迹长度 Stitch length	压脚提升 Presser foot lift	倒缝装置 Reverse feeding device	机针 Needle size	针间距 Needle gauge	缝台高度 Highness of post-bed	旋梭 Rotating hook	润滑方式 Lubrication	电动机 Motor	操作空间 Working space
GC24628-1	2000 r.p.m.	0-7 mm	手动 / 膝控 By hand / knee 7 / 13 mm	手动 By hand	DP × 17 23*	标准 8 mm 特殊 4.8 9.5 12.7 mm 8 mm (Standard) 4.8 9.5 12.7 mm (Special)	178 mm	立式自动润滑 大旋梭 Auto lubricated large hook	半自动润滑 Semi-auto lubricated	370 瓦缝纫机 专用电机 1400 转 / 分 370W Clutch motor 1400r.p.m.	250 × 280 mm
GC24628-1Q	2000 r.p.m.	0-7 mm	气动抬压脚 Pneumatic foot lifting 13 mm	气动 Pneumatic	DP × 17 23*		178 mm	1.6 倍大旋梭 Large vertical hook (1.6 times)		220 伏 550 瓦 伺服电机 220V/550W Servo motor	250 × 280 mm
GC24628-D	2000 r.p.m.	0-7 mm	气动抬压脚 Pneumatic foot lifting 13 mm	气动 Pneumatic	DP × 17 23*		178 mm	立式自动润滑 大旋梭 Auto lubricated large hook	手工润滑 Manual	250 × 280 mm	
GC24628-25	1600 r.p.m.	0-7 mm	气动抬压脚 Pneumatic foot lifting 13 mm	气动 Pneumatic	DP × 17 23*		178 mm	178 mm	178 mm	635 × 280 mm	



GC24628-1 立柱式综合送料针杆离合双针平缝机



特殊规格针间距请在订货时指定
Please specify for special needle gauge when ordering